



ROOFNADOTM

StormTreadTM XW



NEXGENTM
SYNTHETICS

ALL TEMP. ALL WEATHER
PERFORMANCE

RoofnadoTM StormTreadTM XW is a next generation synthetic roofing underlayment for sloped roof applications. StormTreadTM XW has an advanced mechanical slip-resistant walking surface which provides superior steep-slope walkability and increased safety for roofers. In addition, StormTreadTM XW has a uniquely designed coating technology which allows the underlayment to be anchored to the deck prior to using fasteners. StormTreadTM XW is designed for use under asphalt shingles, concrete tiles, all metal panels, synthetic shingles and primed cedar shakes. StormTreadTM XW meets all the code requirements including ASTM D226, ASTM D4869 and AC 188 as required by ICC-ES.

StormTreadTM XW not only protects your roof, it helps protect roofers as well.

Ask for it at your nearest roofing distributor today.



**PRINT
YOUR LOGO[®]
HERE!**

Attract new customers and increase awareness in your local area!

Visit:
www.roofnado.com/dual-logo
for more information

- StormTreadTM XW advanced micro-etched surface technology provides superior steep-slope walkability for roofers
- All temp. all weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 212°F)
- *No stretching around fasteners & no blow-offs!
- Meets the performance requirements of CAN/CSA A220.1
- ICC-ES ESR-4055 | FBC Approved – FL21895
- Class A fire rating - ASTM E108
- Texas Department of Insurance Approved
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- 180 days UV exposure
- High Definition (HD) printing
- Limited Lifetime Warranty



Lifetime
LIMITED WARRANTY



ROOFNADO™

StormTread™ XW



 **Roofnado.com**

Sentry Building Innovations
 1209 Orange Street, Wilmington,
 New Castle, Delaware 19801
 Customer Service: 1-843-735-1773

Test/Standard*

Tensile Strength ASTM D5034
 Tear Strength ASTM D4533
 Liquid Water Transmission ASTM D4869
 Fire Rating ASTM E108
 UV Exposure
 Temperature Range

Typical Value

MD 105 lbs (47.6 kg) | CD 100 lbs (45.4 kg)
 MD 27 lbs (12.25 kg) | CD 24 lbs (10.9 kg)
 Pass
 Class A
 6 Months
 -40° - 212° F

Roll/Pallet Specs

Length per roll: 250' / 76.2 m
 Width per roll: 48" / 1.2 m
 Weight per roll: 33 lbs / 15 kg
 Roll size: 10 sq / 93 m²
 Rolls per pallet/truck: 30 / 1,200
 Pallet weight: 1,040 lbs / 472 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.
 ENG-RN-STXW-DIGITAL-R8 NOV2019

†When correctly installed as per StormTread™ XW installation instructions. All Roofnado™ product installation instructions are available to download or view from our website: www.roofnado.com