



Roofnado™ StormTread™

AnchorDeck™ is a next generation synthetic roofing underlayment for sloped roof applications. AnchorDeck™ coating technology allows underlayment to be anchored to the deck prior to applying fasteners. Innovative high-traction walking surface, excellent durability and many other unique performance features make AnchorDeck™ the smart choice for today's roofing professionals.

AnchorDeck™ is designed for use under asphalt shingles, metal panels and shingles, synthetic shingles and primed cedar shakes. AnchorDeck™ meets all the code requirements including ASTM D226, ASTM D4869 and AC 188 as required by ICC-ES.

Ask for it at your nearest roofing distributor today!

Features & Benefits

- StormTread™ micro-etched surface technology which provides superior steep slope walkability for roofers
- No stretching around fasteners & no blow-offs!
- All temp. All weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 240° F)
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- Meets the performance requirements of CAN/CSA A220.1
- Miami-Dade County Product Control Approved
- FBC Approved – FL21895
- ICC-ES Approved
- Class A Fire Rating - ASTM E108
- Texas Department of Insurance Approved
- 180 Days UV Exposure
- Limited Lifetime Warranty

Test/Standard*

Typical Value

Tensile Strength ASTM D5034	MD 108 lbs (49 kg) CD 115 lbs (52.2 kg)
Tear Strength ASTM D4533	MD 30 lbs (13.6 kg) CD 35 lbs (15.9 kg)
Liquid Water Transmission ASTM D4869	Pass
Fire Rating ASTM E108	Class A
UV Exposure	6 Months
Temperature Range	-40° F to 240° F



Roll/Pallet Specs

Length per roll:	250' / 76.2 m
Width per roll:	48" / 1.2 m
Weight per roll:	39 lbs / 17.7 kg
Roll size:	10 sq / 93 m ²
Rolls per pallet/truck:	25 / 900
Pallet weight:	1,028 lbs / 466.3 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.

†When correctly installed as per installation instructions. All product installation instructions are available to download or view from our website: www.roofnado.com

RN AD ST SS MAR24

**Switch to Roofnado™
and start saving on labor,
time & money.
Contact us today!
www.roofnado.com**

